

## CNV-SNAP-ANO 兼容的驱动器列表:

| 功率 (W) | 驱动器系列    | 型号 (×10 = mA)                           | 后缀       | IP 等级          | 输入电压范围 (Vac) |
|--------|----------|---|----------|----------------|--------------|
| 75     | EUD-075S | 070/105/175/280                         | DT/DV    | IP67           | 90-305       |
| 96     | EUD-096S | 070/105/210/215/350                     | DTA/DVA  | IP67           | 90-305       |
| 110    | SUM-110S | 105/260                                 | MF/MG/MT | IP65           | 90-305       |
| 150    | EUD-150S | 105/210/350/560                         | DTA/DVA  | IP67           | 90-305       |
| 150    | ESD-150S | 105/210/350/560                         | DT/DV    | IP67           | 249-528      |
| 220    | SUM-220S | 530                                     | MF/MG/MT | IP65           | 90-305       |
| 220    | SSM-220S | 530                                     | MF/MG/MT | IP65           | 249-528      |
| 240    | ESD-240S | 100/150/220/320/460<br>/660             | DT/DV    | IP67           | 249-528      |
| 240    | EUD-240S | 105/210/420/670                         | DTA/DVA  | IP67           | 90-305       |
| 330    | SUM-330S | 690                                     | MF/MG/MT | IP65           | 90-305       |
| 330    | SSM-330S | 690                                     | MF/MG/MT | IP65           | 249-528      |
| 400    | NEL-400S | 140                                     | MF/MG/MT | IP65/IP66/IP67 | 180-457      |
| 400    | NEL-400S | 140                                     | MP       | IP20           | 180-457      |
| 400    | NTL-400S | 140                                     | MP       | IP20           | 312-528      |
| 440    | SUM-440S | 920                                     | MF/MG/MT | IP65           | 90-305       |
| 440    | SSM-440S | 920                                     | MF/MG/MT | IP65           | 249-528      |
| 480    | EUM-480S | 140/280/420/560/10A                     | MG/MT    | IP66/IP67      | 90-305       |
| 480    | ESM-480S | 140/280/420/560/10A                     | MG/MT    | IP66/IP67      | 249-528      |
| 600    | EUD-600S | 140/170/210/280/420<br>/560/740/980/12A | DT/DV    | IP67           | 90-305       |
| 680    | EUM-680S | 170/240/350/560/840<br>/15A             | MG/MT    | IP66/IP67      | 90-305       |
| 680    | ESM-680S | 170/240/350/560/840<br>/15A             | MG/MT    | IP66/IP67      | 249-528      |
| 680    | NFM-680S | 270                                     | MG/MT    | IP66/IP67      | 180-528      |
| 680    | NFM-680S | 270                                     | GG/GT    | IP66/IP67      | 180-528      |

| 功率 (W) | 驱动器系列    | 型号 (×10 = mA)       | 后缀    | IP 等级     | 输入电压范围 (Vac) |
|--------|----------|---------------------|-------|-----------|--------------|
| 760    | SSM-760S | 15A                 | MG/MT | IP66/IP67 | 249-528      |
| 760    | SSM-760S | 15A                 | MGS   | IP66/IP67 | 249-528      |
| 760    | SUM-760S | 15A                 | MG/MT | IP66/IP67 | 90-305       |
| 760    | SUM-760S | 15A                 | MGS   | IP66/IP67 | 90-305       |
| 880    | ESM-880S | 280/420/700/11A/20A | MG/MT | IP66/IP67 | 249-528      |
| 880    | ESM-880S | 280/420/700/11A/20A | MGS   | IP66/IP67 | 249-528      |
| 880    | EUM-880S | 280/420/700/11A/20A | MG/MT | IP66/IP67 | 90-305       |
| 880    | EUM-880S | 280/420/700/11A/20A | MGS   | IP66/IP67 | 90-305       |
| 880    | NFM-880S | 350                 | MG/MT | IP66/IP67 | 180-528      |
| 880    | NFM-880S | 350                 | GG/GT | IP66/IP67 | 180-528      |
| 880    | NSM-880S | 270                 | MG/MT | IP66/IP67 | 249-528      |
| 880    | NSM-880S | 270                 | GG/GT | IP66/IP67 | 249-528      |
| 1000   | NEL-1K0S | 400                 | MG/MT | IP66/IP67 | 180-457      |
| 1000   | SUM-1K0S | 400/840/21A         | MG/MT | IP66/IP67 | 90-305       |
| 1000   | SUM-1K0S | 400/840/20A         | MGS   | IP66/IP67 | 90-305       |
| 1000   | SSM-1K0S | 400/840/21A         | MG/MT | IP66/IP67 | 249-528      |
| 1000   | SSM-1K0S | 400/840/20A         | MGS   | IP66/IP67 | 249-528      |
| 1200   | EBM-1K2S | 350/525/740         | MG    | IP66/IP67 | 176-305      |
| 1200   | ESM-1K2S | 350/525/740         | MG/MT | IP66/IP67 | 249-528      |
| 1200   | NFM-1K2S | 480                 | MG/MT | IP66/IP67 | 180-528      |
| 1200   | NFM-1K2S | 480                 | GG/GT | IP66/IP67 | 180-528      |
| 1200   | NSM-1K2S | 350                 | MG/MT | IP66/IP67 | 249-528      |
| 1200   | NSM-1K2S | 350                 | GG/GT | IP66/IP67 | 249-528      |
| 1500   | NSM-1K5S | 480                 | MG/MT | IP66/IP67 | 249-528      |
| 1500   | NSM-1K5S | 480                 | GG/GT | IP66/IP67 | 249-528      |
| 1500   | SUM-1K5S | 600/12A/31A         | MG/MT | IP66/IP67 | 90-305       |

注：上表中仅针对具有代表性的产品做了兼容性测试。如有任何问题，敬请联系我司咨询。

20241014